



## GMJJ2.EX27291 Storage Containers for Extinguishing System Units - Component

[Page Bottom](#)

### Storage Containers for Extinguishing System Units - Component

[See General Information for Storage Containers for Extinguishing System Units - Component](#)


**SWASTIK SYNERGY ENGINEERING PRIVATE LIMITED**

EX27291

No. 302 Business Suites 9 S. V. Road Santacruz West Next to RAAS  
Mumbai, 400054 INDIA

Type	Max Volume Cu. Ft. (Ltrs.)	Cylinder Diameter Inch. (mm.)
IS 7285 250 Bar - P/N SSE 9250001	0.05 (1.50)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250002	0.07 (2.00)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250003	0.08 (2.20)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250004	0.09 (2.50)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250006	0.11 (3.00)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250008	0.12 (3.50)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250010	0.14 (4.00)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250011	0.16 (4.50)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250014	0.18 (5.00)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250016	0.19 (5.50)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250018	0.21 (6.00)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250020	0.23 (6.50)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250021	0.24 (6.80)	5.50 (139.70)
IS 7285 250 Bar - P/N SSE 9250022	0.25 (7.00)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250023	0.26 (7.50)	4.25 (108.00)
IS 7285 250 Bar - P/N SSE 9250028	0.36 (10.20)	5.50 (139.70)
IS 7285 250 Bar - P/N SSE 9250030	0.48 (13.50)	5.50 (139.70)
IS 7285 245 Bar - P/N SSE 9250039	0.78 (22.00)	9.13 (232.00)
IS 7285 245 Bar - P/N SSE 9250052	1.20 (34.00)	9.13 (232.00)
IS 7285 334 Bar - P/N SSE 9250053	1.20 (34.00)	9.13 (232.00)
IS 7285 250 Bar - P/N SSE 9250057	1.20 (34.00)	9.13 (232.00)
IS 7285 250 Bar - P/N SSE 9250069	1.41 (40.00)	9.13 (232.00)
IS 7285 245 Bar - P/N SSE 9250071	1.42 (40.20)	9.13 (232.00)
IS 7285 245 Bar - P/N SSE 9250079	1.55 (44.00)	9.13 (232.00)
IS 7285 245 Bar - P/N SSE 9250092	1.65 (46.70)	9.13 (232.00)
IS 7285 334 Bar - P/N SSE 9250097	1.77 (50.00)	9.13 (232.00)
IS 7285 334 Bar - P/N SSE 9250142	2.40 (68.00)	10.51 (267.00)
IS 7285 490 Bar - P/N SSE 9250143	2.40 (68.00)	10.51 (267.00)

IS 7285 250 Bar - P/N SSE 9250146	2.40 (68.00)	10.51 (267.00)
IS 7285 334 Bar - P/N SSE 9250162	2.83 (80.00)	10.51 (267.00)
IS 7285 490 Bar - P/N SSE 9250163	2.83 (80.00)	10.51 (267.00)
IS 7285 334 Bar - P/N SSE 9250187	3.53 (100.00)	14.02 (356.00)
IS 7285 334 Bar - P/N SSE 9250196	4.24 (120.00)	14.02 (356.00)
IS 7285 334 Bar - P/N SSE 9250206	4.94 (140.00)	14.02 (356.00)
IS 7285 334 Bar - P/N SSE 9250212	5.30 (150.00)	14.02 (356.00)
IS 7285 334 Bar - P/N SSE 9250223	7.06 (200.00)	15.98 (406.00)
ISO 9809 225 Bar - P/N SSE 9250229	0.85 (24.00)	9.13 (232.00)
ISO 9809 225 Bar - P/N SSE 9250230	1.41 (40.00)	9.13 (232.00)
IS 7285 334 Bar - P/N SSE 9250235	5.65 (160.00)	14.02 (356.00)
IS 7285 334 Bar - P/N SSE 9250236	6.36 (180.00)	14.02 (356.00)
ISO 9809 225 Bar - P/N SSE 9250237	1.65 (46.70)	9.13 (232.00)

Marking: Company name or identification, type designation and the Recognized Component Mark 

Last Updated on 2017-02-23

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".